


**ALL OUR GAUGE TOLERANCES FOR
PLUG GAUGES, RING GAUGES AND SNAP GAUGES
ARE AS PER IS 3455:1975
AND IS 919:1963.**




PLAIN PLUG GAUGES :

Range: 0.30 to 1000 mm. From 1000 - 2000mm available on request.
0.30 - 10.00mm - Reversible Pin Type Plug
10.01 - 40.00mm - Taper Lock Design IS 6137:1987
40.01 - 100.00mm - Disc Double Ended IS 6244:1980
100.01 - 300.00mm - Plate Type Plug S/E GO & NOGO - Separate - JE Design
Above 300.01mm - Progressive Type - JE Design



THREAD MEASURING WIRES

Range: 0.17 to 3.20 mm - 16 sizes, 0.17 to 6.35mm - 21 sizes
The above wires can be supplied in sets of two or three wires. Odd size wires in inches or millimetres can also be supplied either in sets of two or three wires.
The standard set consists of following 16 or 21 sizes in millimetres.
Specification: IS 6311:1978



PLAIN RING GAUGES - GO & NOGO RINGS

Range: 1.00 to 600mm
Specification: As per IS3485:1983. Above 315mm as per JE Design.

MASTER SETTING RINGS

Range: 1.00 to 600mm
Specifications: As per IS 3485:1983. Above 315mm as per JE Design



PLAIN SETTING MASTERS

Range: 1.00 mm to 300.00mm. Above 300mm available on request.
Specification: As per IS 4349:1987



THREAD DEPTH GAUGES

Range - ISO metric, Unified, Taper (Formally NPT and BSPT), BSW-BSF, B.S. Cycle, B.A. screw and G series (Formally BSPF) thread gauges.
Thread gauges are available in both plugs (from diameter 1.60mm - 200.00mm) and ring types (from diameter 2.00mm - 200.00mm)
Specifications: The thread gauges are made in accordance with National and International standards such as ANSI, BS, IS, etc